

### **Amendments to the Claims:**

1. (Currently Amended) A data processing system having:  
at least one processor chip including a processor unit and an internal data cache, and  
an interface external to the internal data cache and configured to receive cache mirror  
data from the processor chip, the interface further configured to discard all the cache mirror data  
to be written to an external memory received from the processor chip ~~without writing any of the~~  
so that cache mirror data is never written to ~~[[the]]~~ external memory during operation of the  
processor chip.
2. (Previously Presented) A data processing system according to claim 1 in which the  
interface is coupled to a memory, the interface passing data to the processor chip during  
initialization.
3. (Original) A data processing system according to claim 1 further including one or more  
further processing chips which have read/write access to external memory.
4. (Currently Amended) A method of operating a processing chip having a processor, an  
internal data cache and a cache controller for transmitting cache mirror data write instructions  
out of the processing chip ~~integrated circuit~~, the method including discarding the write  
instructions ~~so that without writing any~~ cache mirror data is never written to ~~[[an]]~~ external  
memory during operation of the processing chip; and arranging for the program code operated by  
the processor to require only the data cache as memory.

5. (Previously Presented) A data processing system according to claim 1 wherein the at least one processor chip comprises exactly one processor chip.

6. (Previously Presented) A data processing system according to claim 1 wherein the at least one processor chip comprises two processor chips.

7. (Previously Presented) A data processing system according to claim 1 wherein the processor chip further includes an internal cache controller coupled between the internal data cache and the processor unit.

8. (Currently Amended) A data processing system comprising:  
a processor chip including an internal processor coupled to an internal data cache;  
an external memory; and  
an interface external to the internal data cache and coupled between the processor chip and the external memory, the interface configured to receive memory data from the external memory and transfer the memory data to the processor chip, the interface further configured to receive ~~processor~~ internal data cache mirror data from the processor chip and discard all the ~~processor~~ internal data cache mirror data to be written to the external memory so that ~~without writing any of the processor~~ internal data cache mirror data is never written to ~~[[an]]~~ external memory.

9. (Previously Presented) The system of claim 8 and further comprising a control circuit coupled to the interface circuit, the control circuit providing a control signal to indicate whether data received by the interface should be discarded.

10. (Previously Presented) The system of claim 9 wherein the control circuit comprises a decoder.

11. (Previously Presented) The system of claim 8 and further comprising:  
a second processor chip that includes an internal processor coupled to an internal cache;  
and  
a second interface, wherein the second processor chip is coupled to the external memory through the second interface.

12. (Previously Presented) The system of claim 11 and further comprising a system bus coupled to the processor chip, the second processor chip, the interface, and the second interface.

13. (Previously Presented) The system of claim 12 and further comprising a third processor chip coupled to the system bus.

14. (Previously Presented) The system of claim 13 wherein the third processor chip comprises a master processing unit and wherein the processor chip and the second processor chip comprise slave processing units.

15. (Previously Presented) The system of claim 14 and further comprising a second external memory directly coupled to the system bus.

16. (New) A method of operating a data processing system having a plurality of integrated circuits, each integrated circuit having a processor, an internal data cache, and a cache controller, the method comprising:

transmitting cache mirror data write instructions from a first cache controller of a first integrated circuit to an external memory interface, wherein the external memory interface is located outside the first integrated circuit; and

discarding the first cache mirror data write instructions at the external memory interface so that cache mirror data is never written to external memory during operation of the first processor.

17. (New) The method of claim 16, further comprising:

transmitting second cache mirror data write instructions from a second cache controller in a second integrated circuit to the external memory interface;

writing the second cache mirror data write instructions from the external memory interface to external memory.

18. (New) The method of claim 17, further comprising:

determining if a task requires a read/write memory that is larger than an internal data cache size; and

allocating the task to the first integrated circuit or to the second integrated circuit based upon the determining step.